



ECUADOR

1700 ECUATEPI
3 2 8 2 8 3 7 4



PANAMA

Sitio web: www.ecuatepi.com

E- Mail: info@ecuatepi.com

Electric Solenoid

DESCRIPTION

The Electric Solenoid Valve is a normally closed valve that requires electrical energy to open. This opening vents the pressure from the top of the piston in the cylinder valve, allowing the piston to slide upward and commence cylinder discharge. The Electric Solenoid Valves are available in 6 VDC, 12 VDC, 24 VDC and 120 VAC. The source of the electrical energy will determine the number and rating of the electrical solenoid used. The solenoid circuit must be supervised for a break in the wiring, a ground or a short circuit. The cylinder discharge valve that is equipped with a solenoid valve is to be connected to a Control Panel that is UL Listed for releasing devices and compatible with Orient Fire Suppression equipment.

Prior to wiring the solenoid to the actuation circuit, check to be sure.



NOTE: Two 12 VDC solenoids can be wired in series in a 24 VDC actuating circuit.

Connect solenoid pigtails to actuation circuit wires with wire nuts within a junction box or by means designated by the authority having jurisdiction.

Whenever an Electric Solenoid is used as the sole means of actuation, a top plug must be used to seal the top of the cylinder valve.

Part Number	Description	Electrical Rating
DCI 50025-1	Electric Solenoid	12 VDC 0.385 Amp
DCI 50025-1E	Electric Solenoid	12 VDC 0.385 Amp (Explosion Proof)
DCI 50025-2	Electric Solenoid	24 VDC 0.32 Amp
DCI 50025-2E	Electric Solenoid	24 VDC 0.32 Amp (Explosion Proof)
DCI 50025-3	Electric Solenoid	120 VAC 0.16 Amp
DCI 50025-3E	Electric Solenoid	120 VAC 0.16 Amp (Explosion Proof)
DCI 50025-4	Electric Solenoid	6 VDC 1.52 Amp
DCI 50025-4E	Electric Solenoid	6 VDC 1.52 Amp (Explosion Proof)
DCI 91225-1	Electric Solenoid	1,200 LB. 12 VDC
DCI 91225-2	Electric Solenoid	1,200 LB. 24 VDC

TECNICAS ECUATORIANAS DE PROTECCIÓN CONTRA INCENDIOS

ECUATEPI S.A.

Pag. 1

